



## What is vis|ability System Manager?

**System Manager** manages the configuration of sources of content, like video walls and display endpoints, externally controlled devices, user profiles, and permissions, in a central database, and serves them to authenticated components of the vis|ability software platform.

- ✓ **Centralized Management**  
The ultimate hub for complete control: manage Users, Sources, Displays, and Integrations seamlessly from a single interface.
- ✓ **Robust Security**  
Access is protected through a secure, authenticated interface, ensuring administrative actions remain in trusted hands.
- ✓ **High Availability**  
Deploy System Manager with unmatched flexibility—physical or virtual configurations tailored to your redundancy and uptime requirements.

## Key Benefits

- + **Expandability**  
Effortlessly scale your system—add unlimited information to meet evolving needs without limitations.
- + **Simplicity**  
Designed with an intuitive admin interface, enabling administrators to expand the system quickly and easily with minimal effort.
- + **Resilience**  
Built for secure disaster recovery from any location, leveraging virtual or clustered physical machines to ensure continuous operation and reliability.



Model	VSM-300 1RU Rackable vis ability Display Node to drive up to 16 HD or 4 4K displays.	Virtual Machine System Manager virtual machine requirements.
Dimensions	H 1.68" (42.8 mm) x W 18.98" (482 mm) x D 23.19" (589.1 mm) with Bezel or D 22.74" (577.6 mm) without Bezel Weight 19.27lb (8.74 kg)	N/A
CPU	Intel Core i7-8700, (6 Core, 12MB Cache, 3.20GHz, 4.6GHz Turbo w/UHD Graphics 630)	2 processors, 4 cores each
Memory	32GB 4x8GB DDR4 2666MHz UDIMM Non-ECC Memory	16GB RAM
Graphics Output	Nvidia Quadro P2200, 5GB, 4 DP (3930, xx20)	64bit graphics VDI
Graphics Input	CPU/GPU IP decode up to 24 HD streams	64bit graphics VDI
Integrated Graphics	Integrated Intel HD Graphics 630 (1xHDMI, 1xDP) - for 'service' screen only	N/A
Fixed Drives	2x 2.5" 256GB SATA Class 20 Solid State Drive	N/A
RAID Controller	N/A	N/A
Network	Integrated Intel 10/100/1000 Mb/s Ethernet (RJ45) Integrated Aquantia 10 GB/s Ethernet (RJ45)	Dual NIC
Power Supply	Dual Hot-plug Redundant Power Supply 550W	N/A
Operating System	Windows 10 Pro 64bit	N/A
Operating Environment	Temperature <i>Operating</i> : 10–45°C (50°F–113°F) <i>Storage</i> : -40°C to 65°C (-40°F to 149°F) Humidity <i>Operating</i> : 10% to 85% (Max dew point temperature = 40°C) (noncondensing). <i>Storage</i> : 10% to 90% (Max dew point temperature = 60°C) (noncondensing)	N/A